



OUTPUT
135 WATTS R.M.S.
TOTAL LOAD
IMPEDANCE
4 OHMS MIN.

500V. STANDBY ON
520 V. STANDBY OFF

100 TO 260 V.
EXPORT VERSIONS
ONLY (50/60 HZ)

FENDER MUSICAL INSTRUMENTS
CBS MUSICAL INSTRUMENTS
A DIVISION OF CBS INC.
FULLERTON, CALIFORNIA
U.S.A.

CAUTION:
500 VOLTS AVAILABLE DISCONNECT POWER SUPPLY
AND ALLOW AT LEAST 30 SECONDS FOR VOLTAGES
TO BLEED OFF BEFORE SERVICING AMPLIFIER.

CBS	
MUSICAL INSTRUMENTS FULLERTON, CALIFORNIA	
— SCHEMATIC —	
135 WATTS RMS P.A. 135 AMP	
DWG. NO. 014335	REV 1

- INPUT JACKS 011028
 △ USED IN SOME VERSIONS.
 6. WHEN INSTALLING NEW 6L6'S RESET O.T. MATCHING FOR MIN. HUM.
 5. WITH ALL CONTROLS SET AT MAXIMUM, (XX MV) DENOTES, TYPICAL 400HZ SIGNAL REQUIRED FOR 10 WATTS OUTPUT AND 1000-MV TO REVERB INPUT COIL-ALL CONTROLS MAX.
 (XX MV) DENOTES REVERB DRIVER SIGNAL, EXCLUSIVELY.
 4. BASS AND TREBLE CONTROLS ARE P/N021857.
 3. FENDER P/N FOR CONTROLS INDICATED.
 2. ALL CAPACITORS AT LEAST 600V, W.V.D.C.
 1. ALL RESISTORS ARE 1/2 WATTS ± 10%.

NOTES: UNLESS OTHERWISE SPECIFIED